

HIGH FLOW SERIES

Hotsy's High Flow Series features up to an 8.0 GPM flow rate and 3000 PSI to blast through the toughest jobs on farms and construction sites, perfect for waste and debris removal. Our rugged and economical cold water pressure washer features a high-quality triplex pump and is equipped with a Honda engine for quiet, reliable performance. Three gas models allow you to find the right machine for your needs and these skid units can be mounted for easy mobile transport. Put your High Flow on wheels with our flat-free tire cart kit. All models equipped with a 50' hose, chemical injector and 12V battery.

- Belt-drive
- Reliable Honda GX engine with three-year warranty
- Modular design - change to stationary unit with optional skid feet kit
- Flat-free tires and steel cage
- Machine will fit up to a 100' hose reel
- ETL certified to UL-1776 safety standards



5/30 G shown with optional flat-free tire cart kit and optional 100' capacity hose reel



MODEL	PART NO.	GPM	PSI	ENGINE MODEL	CCs	PUMP MODEL	HOSE (FT)	DIMENSIONS (LXWXH)	SHIP WT (LBS)
HHD 5/30 G	1.107-377.0	5.0	3000	Honda GX630	688	6036R	50'	50" X 40" X 58"	426
HHD 6/30 G	1.107-378.0	6.0	3000	Honda GX630	688	6036R	50'	50" X 40" X 58"	426
HHD 8/30 G	1.107-379.0	8.0	3000	Honda GX690	688	8043R	50'	50" X 40" X 58"	443

OPTIONS

PART NO.	DESCRIPTION
8.929-069.0	Flat-Free Cart Kit
8.750-478.0	100' Capacity Hose Reel
8.750-247.0	Trigger Gun, model M407
8.925-132.0	Hose, 3/8" X 50' 2W 6000 PSI SW/SO/CPL (5/30 & 6/30)
8.925-134.0	Hose, 1/2" X 50' 2W 5000PSI SW/SO/CPL (8/30)
9.802-216.0	Injector Chem, non adjustable, 3-5 GPM (5/30)
8.757-724.0	Injector Chem, non adjustable, 5-9 GPM (6/30 & 8/30)
8.925-229.0	Legacy, 100' x 3/8" ID, 6000 PSI, 2-wire, smooth cover, black high pressure hose

BD SERIES & HHD DIESEL MODEL

BELT DRIVE

The BD Series is the most rugged cold water pressure washer on the market with its all-steel frame and cage, Hotsy belt-drive, triplex pump and cleaning power of up to 5000 PSI. Four gas models make up what is Hotsy's most durable cold water line-up ever. All models equipped with a 50' hose.

- Honda, Vanguard or new Kohler diesel engine
- Small & large roll cage design
- Totally enclosed belt guard
- VRT3 unloader
- Flat-free tires for easy handling
- Plated steel high-pressure wand with side handle
- ETL certified to UL-1776 safety standards



BD Series shown in large cage (4-wheel) version. Small cage 2-wheel version also available.



Diesel model uses the High Flow frame and comes as a skid, as shown



MODEL	PART NO.	GPM	PSI	ENGINE MODEL	CCs	PUMP MODEL	FRAME	NO. WHEELS	DIMENSIONS (LXWXH)	SHIP WT (LBS)
BD-373539	1.107-021.0	3.7	3500	Honda GX390	389	HM4035R.3	Small Cage	2	42"x26"x30"	275
BD-404029	1.107-022.0	4.0	4000	Briggs VAN 16	479	HX5843R.2	Large Cage	4	46"x30"x36"	360
BD-405039E*	1.107-023.0	4.0	5000	Honda GX630	688	HX5450R	Large Cage	4	46"x30"x36"	417
BD-455039E*	1.107-024.0	4.5	5000	Honda GX690	688	HX5450R	Large Cage	4	46"x30"x36"	430
COMING SOON										
HHD 3.4/30 D	1.107-382.0	3.4	3000	Kohler KD440	442	3540R	High Flow	4	48"x27"x42"	155

*E = Electric Start

OPTIONS

PART NO.	DESCRIPTION
8.904-109.0	E-Zee Hose Reel Kit* 100' (Small Cage)
8.904-110.0	E-Zee Hose Reel Kit* 100' (Large Cage)
8.904-113.0	5000 PSI Hose Reel Kit,* (Large Cage)
8.904-115.0	5000 PSI Dual Hose Reel Kit,* † (large cage)
8.929-069.0	Flat-Free Cart Kit
8.750-478.0	100' Capacity Hose Reel

*Includes hose reel and mounting hardware

†Includes garden hose reel and high-pressure hose reel

BX SERIES

BELT DRIVE

The BX Series is similarly rugged to the BD Series, but more compact. Powered by Honda engines, the BX series delivers cleaning power up to 3500 PSI and an all-steel frame protected by a durable powder coat finish. The Hotsty triplex pumps carry a 7-year limited warranty. Equipped with a 50' hose.

- Honda engines
- Totally enclosed belt guard
- Flat-free tires for easy handling
- Insulated steel high-pressure wand w/ side handle
- ETL-certified to UL-1776 safety standards



Shown with optional hose reel & mounting kit



MODEL	PART NO.	GPM	PSI	ENGINE MODEL	CCs	START	PUMP MODEL	FRAME	DIMENSIONS (LXWXH)	SHIP WT (LBS)
BX-282039	1.107-026.0	2.8	2000	Honda GX160	163	Recoil	HB3030R	Small Chassis	37"x21"x24"	152
BX-373539	1.107-028.0	3.7	3500	Honda GX390	389	Recoil	HM4035R.3	Large Chassis	45"x26"x24"	240

OPTIONS

PART NO.	DESCRIPTION
8.929-062.0	Detergent Injector (up to 3 GPM)
9.802-225.0	Detergent Injector (over 3 GPM)
8.723-636.0	Detergent nozzle
8.904-103.0	EZ Hose Reel Kit 100' (incl. reel & mounting hardware)

DB SERIES

DIRECT DRIVE

The DB Series is the most compact, affordable alternative in the cold water line featuring a direct-drive triplex pump. All models are powered by reliable Honda engines. Lightweight design and tubed pneumatic tires make for easy maneuvering.

- Honda GX engines
- Steel frame
- 10" tubed pneumatic tires for easy handling
- Protected by a powder coat finish
- Insulated, 2-piece steel high-pressure wand
- ETL-certified to UL-1776 safety standards



Shown with optional hose reel & mounting kit



MODEL	PART NO.	GPM	PSI	ENGINE MODEL	CCs	PUMP MODEL	HOSE (FT)	DIMENSIONS (LXWXH)	SHIP WT (LBS)
DB-232439	1.107-031.0	2.3	2400	Honda GX160	163	HP2535G	50	35"x21"x24"	140
DB-252739	1.107-032.0	2.5	2700	Honda GX200	196	HP2535G	50	35"x21"x24"	145
DB-303039	1.107-033.0	3.0	3000	Honda GX270	270	HP3035G1	50	35"x21"x24"	175
DB-354039	1.107-222.0	3.5	4000	Honda GX390	390	HS354093	50	35"x21"x24"	179
DB-383539	1.107-034.0	3.8	3500	Honda GX390	390	HS4040G3	50	35"x21"x24"	179

OPTIONS

PART NO.	DESCRIPTION
8.904-105.0	EZ Hose Reel Kit 100' (includes reel & mounting hardware)

HC SERIES HANDHELD

DIRECT DRIVE

The HC Series is the handheld model of the gasoline-powered line, delivering cleaning capability up to 2400 PSI. The HC is driven by a Honda engine and features a reliable direct-drive triplex pump and is ETL safety certified.



- Honda engine
- Direct-drive high-pressure pump
- Cleaning power up to 2400 PSI
- Weighs 80 lbs
- Convenient carrying handle



MODEL	PART NO.	GPM	PSI	ENGINE MODEL	CCs	PUMP MODEL	HOSE (FT)	DIMENSIONS (LXWXH)	SHIP WT (LBS)
HC-232439	1.107-036.0	2.3	2400	Honda GX160	163	HP2535G	25	20"x16"x17"	95

HD SERIES

DIRECT DRIVE **BELT DRIVE**

The HD Series are Hotsy's modular cold water pressure washers with corrosion resistant aluminum frame. Wheels can be removed allowing for easy trailer mounting. Models are available in belt or direct drive and powered by Honda GX engines. The HD series features a durable VTR3 unloader with bypass loop, commercial duty pump and a 50' hose.



- Honda GX engines
- Modular design converts to skid
- VTR3 unloader with bypass loop
- Flat-free tires for easy handling
- Downstream chemical injection
- ETL certified to UL-1776 safety standards



MODEL	PART NO.	GPM	PSI	ENGINE MODEL	CCs	START	PUMP MODEL	DRIVE	HOSE (FT)	DIMENSIONS V(LXWXH)	SHIP WT (LBS)
HD 3.0/27 G	9.807-711.0	3.0	2700	Honda GX200	196	Recoil	LP3035	Direct	50	41"x22"x24"	112
HD 3.5/35 G	9.807-712.0	3.5	3500	Honda GX270	270	Recoil	LP3535G.1	Direct	50	41"x22"x24"	130
HD 4.0/40 G	9.807-713.0	4.0	4000	Honda GX390	389	Recoil	LS4040G.3	Direct	50	43"x26"x27"	149
HD 4.0/40 Ge	9.807-714.0	4.0	4000	Honda GX390	389	Electric	LS4040G.3	Direct	50	43"x26"x27"	158
HD 3.0/27 GB	9.807-715.0	3.0	2700	Honda GX200	196	Recoil	LP3035G	Belt	50	41"x22"x24"	123
HD 3.5/35 GB	9.807-716.0	3.5	3500	Honda GX270	270	Recoil	LM3540R.3	Belt	50	41"x22"x24"	156
HD 4.0/40 GB	9.807-717.0	4.0	4000	Honda GX390	389	Recoil	LM3840R.3	Belt	50	43"x26"x27"	160
HD 4.0/40 GeB	9.807-718.0	4.0	4000	Honda GX390	389	Electric	LM3840R.3	Belt	50	43"x26"x27"	196

OPTIONS	
PART NO.	DESCRIPTION
9.807-750.0	37.5" Handle
9.807-751.0	Handle with Hose Reel
9.807-752.0	Hose Hook

OPTIONS	
PART NO.	DESCRIPTION
9.807-753.0	Wand Holder
9.807-754.0	Skid Mount Feet (set of 4)

SKID OPTIONS

Dealer assembly required. Pressure washer sold separately.

The perfect accompaniment to Hotsy HD Series pressure washers – these mild steel skids offer two configurations: skid with a 50 gallon water tank and 100' hose reel OR skid with two 100' hose reels. The HD Skids fit within a standard UTV / ATV bed when ordering the direct drive models as depicted below.

NOTE: Belt drive models extend beyond the frame and are not recommended. Skid feet included.



DESCRIPTION	PART NO.	FRAME MATERIAL	WATER TANK	HOSE REEL	COMPATIBLE PRESSURE WASHER (SOLD SEPARATELY)	DIMENSIONS (LXWXH)	SHIP WT (LBS)
One 100' Hose Reel & 50 gallon Water Tank	9.807-835.0	Mild Steel	50 gallon	1	HD 3.0/27 G 9.807-711.0 HD 3.5/35 G 9.807-712.0 HD 4.0/40 G 9.807-713.0	40"x48"x35"	180 (excluding pressure washer)
Two 100' Hose Reels	9.807-840.0	Mild Steel	Not Included	2	HD 3.0/27 G 9.807-711.0 HD 3.5/35 G 9.807-712.0 HD 4.0/40 G 9.807-713.0	40"x48"x35"	172 (excluding pressure washer)

CWC SERIES

BELT DRIVE

The CWC Series is a completely self-contained, stationary, electric-powered, cold water washer with programmable smart control, upstream detergent injector and ETL safety certification. Remote ready for wash bays. All models equipped with a 50' hose. Ideal for the food industry since hot water can be used.

- *Smart Relay Control provides control over run time, auto start/stop and shut down functionality*



MODEL	PART NO.	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMP	PUMP MODEL	HOSE (FT)	SHIP WT (LBS)
CWC-53	1.106-572.0	4.0	3000	7.5	1725	230/1	36	HM4030R.3	50	340
CWC-54	1.106-573.0	4.0	3000	7.5	1725	230/3	23	HM4030R.3	50	340
CWC-55	1.106-574.0	4.0	3000	7.5	1725	460/3	11	HM4030R.3	50	340
CWC-56	1.106-575.0	4.0	3000	7.5	1770	575/3	9	HM4030R.3	50	340
CWC-63	1.106-576.0	5.0	2000	7.5	1725	230/1	36	HM4035R.3	50	340
CWC-64	1.106-577.0	5.0	2000	7.5	1725	230/3	18	HM4035R.3	50	340
CWC-65	1.106-578.0	5.0	2000	7.5	1725	460/3	9	HM4035R.3	50	340
CWC-66	1.106-579.0	5.0	2000	7.5	1770	575/3	8	HM4035R.3	50	340

OPTIONS

PART NO.	DESCRIPTION
8.924-814.0	R-Con Wireless Remote Kit (1 remotes/1 receiver)
8.925-072.0	R-Con Wireless Remote Kit (2 remotes/1 receiver)
8.924-878.0	Wall Mount Remote Bracket for R-Con
8.756-329.0	Replacement Remote (transmitter only)

See page 37 for stainless steel and other configured options thru the Specials Dept.

1700 SERIES

BELT DRIVE

The 1700 Series offers the most reliable, stationary, electric-powered, cold water pressure washer featuring a Hotsy belt-drive, triplex pump with 7-year limited warranty, insulated variable pressure wand and ETL safety certification. All models equipped with a 50' hose.

- Electric motor, 2-10 HP
- Downstream detergent injector
- Insulated SS variable pressure wand
- Option-ready for Time Delay Shutdown or Auto Start/Stop



Shown with optional stainless steel cabinet



Model 1710 shown with optional wheel kit & chemical rack (PN 9.801-031.0). Note: this is not the short stand.

1700 Series shown with optional hose reel kit, (PN 8.903-039.0), Tall Floor Stand (PN 9.801-034.0), caster wheel kit (PN 9.801-035.0) and stainless steel base and cover (PN 8.903-042.0).



MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	AMPS	PUMP MODEL	PORTABILITY	DIMENSIONS (LXWXH)	SHIP WT (LBS)
1710	1.106-511.0	2.8	1000	2	120/1	20	HB3030R	Optional	31"x21"x16"	200
1720	1.106-512.0	3.9	2000	6	230/1	28	HM4030R.3	Optional	31"x21"x16"	275
1722	1.106-513.0	3.9	2000	6	208/1	30	HM4030R.3	Optional	31"x21"x16"	250
1723	1.106-514.0	3.9	2000	6	208/3	16	HM4030R.3	Optional	31"x21"x16"	250
1724	1.106-515.0	3.9	2000	6	230/3	16.8	HM4030R.3	Optional	31"x21"x16"	250
1725	1.106-516.0	3.9	2000	6	460/3	8	HM4030R.3	Optional	31"x21"x16"	250
1726	1.106-590.0	3.9	2000	7.5	575/3	6.6	HM4030R.3	Optional	31"x21"x16"	275
1743	1.106-529.0	4.8	3000	10	208/3	31.3	HM4035R.3	Optional	31"x21"x16"	302
1744	1.106-530.0	4.8	3000	10	230/3	26.8	HM4035R.3	Optional	31"x21"x16"	300
1745	1.106-531.0	4.8	3000	10	460/3	15	HM4035R.3	Optional	31"x21"x16"	315
1746	1.106-591.0	4.8	3000	10	575/3	9.6	HM4035R.3	Optional	31"x21"x16"	290
1753	1.106-534.0	5.6	2500	10	208/3	31.3	HX9536R.2	Optional	31"x21"x16"	320
1754	1.106-535.0	5.6	2500	10	230/3	26.8	HX9536R.2	Optional	31"x21"x16"	310
1755	1.106-536.0	5.6	2500	10	460/3	13.5	HX9536R.2	Optional	31"x21"x16"	310
1756	1.106-592.0	5.6	2500	10	575/3	10.3	HX9536R.2	Optional	31"x21"x16"	310

OPTIONS	
PART NO.	DESCRIPTION
9.801-031.0	Kit, 1700 Wheel w/Chemical Rack (black)
8.904-527.0	Kit, 1700 Wheel w/Chemical Rack (stainless steel)
9.801-033.0	Kit, 1700 Wall Mount
9.801-034.0	Kit, 1700 Floor Stand, Tall (20 3/4"W x 29"D x 36"H)
9.801-035.0	Kit, Caster Wheels for 1700 Floor Stand
8.903-039.0	Kit, Hose Reel w/Bracket for 1700 Stand & Wall Mount Kits
8.903-040.0	Kit, 1700 Floor Stand, Short (20 3/4"W x 29"D x 24"H)
8.903-043.0	Kit, 1700 Wall Mount, Stainless Steel
8.903-041.0	Time Delay for Models 172x, 173x, 174x*†
8.925-518.0	Automatic Stop/Start for Model 1726*†
8.925-517.0	Automatic Stop/Start for Model 1746*†
8.925-519.0	Time Delay for Models 1726, 1746*†

OPTIONS	
PART NO.	DESCRIPTION
8.903-045.0	Time Delay Shut Down for Model 1710*†
8.903-044.0	Time Delay Shut Down for Models 175x*†
8.903-042.0	Stainless Steel Base & Cover for Models 172x, 174x, 175x †
8.923-421.0	Stainless Steel Base & Cover for Model 1710 †
8.903-047.0	Automatic Stop/Start for Models 1710, 172x*†
8.903-048.0	Automatic Stop/Start for Models 175x*†
8.903-046.0	Automatic Stop/Start for Models 173x, 174x*†
8.903-617.0	Kit, 1700 Floor Stand, Tall, Stainless Steel
8.903-521.0	Kit, Hose Reel for Wheel Kit, 100 ft. (excludes hose)
8.925-521.0	Automatic Stop/Start for Model 1756*†
8.925-522.0	Time Delay for Model 1756*†

*Time Delay Shutdown and Auto Start/Stop cannot be combined on the same machine
†Factory installed

BDE SERIES

BELT DRIVE

The BDE Series is the electric equivalent of the BD Series. Hotsy belt-drive, triplex pump and cleaning power of 5000 PSI. Both models feature the large cage frame and are equipped with a 50' hose.

- 1765 RPM Motor
- Totally enclosed belt guard
- 12' cord length
- NEMA 4-Electrical Box
- Flat-free tires for easy handling
- Plated steel high-pressure wand w/ side handle
- ETL certified to UL-1776 safety standards



MODEL	PART NO.	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMPS	PUMP MODEL	PUMP RPM	HOSE (FT)	DIMENSIONS (LXWXH)	SHIP WT (LBS)
BDE-505009B	1.107-085.0	5.0	5000	20	1765	230/3	48	HX5450R	1650	50	46"x30"x36"	524
BDE-505009C	1.107-086.0	5.0	5000	20	1765	460/3	26	HX5450R	1650	50	46"x30"x36"	524

OPTIONS

PART NO.	DESCRIPTION
8.904-110.0	E-Zee Hose Reel Kit*100' (large cage)
8.904-113.0	5000 PSI Hose Reel Kit,* (large cage)
8.904-115.0	5000 PSI Dual Hose Reel Kit,*† (large cage)

*Includes hose reel and mounting hardware

†Includes garden hose reel and high-pressure hose reel

HD SERIES ELECTRIC CART

DIRECT DRIVE

The HD Series electric carts are corrosion-resistant aluminum cold water pressure washers that easily convert from a cart to a skid for maximum cleaning versatility. Low profile handle and compact footprint. Includes bypass loop for additional pump protection.



- Aluminum frame
- Converts easily to skid style frame
- Flat-free tires for easy handling
- Downstream chemical injection
- ETL safety certification



MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	MOTOR RPM	AMPS	PUMP MODEL	HOSE (FT)	DIMENSIONS (LXWXH)	SHIP WT (LBS)
HD 1.9/13 Ed	9.801-798.0	1.9	1300	2	120/1	1725	20	LF2030S	50	35"x21"x24"	196
HD 2.0/10 Ed	9.801-797.0	2.0	1000	1.5	120/1	1725	15	LF2030S	50	35"x21"x24"	212
HD3.0/10 Ed	9.801-799.0	3.0	1000	2	120/1	1725	20	LF2830S	50	35"x21"x24"	219
HD 3.5/20 Ea	9.801-800.0	3.5	2000	5	230/1	3450	22	LF3530F	50	35"x21"x24"	220

OPTIONS

PART NO.	DESCRIPTION
9.807-754.0	Skid Feet (set of 4)
9.807-750.0	37.5" Long Handle
9.807-751.0	Handle with Hose Reel
9.807-752.0	Hose Storage Hook
9.807-753.0	Wand Holder

ET SERIES HANDHELD

DIRECT DRIVE

The ET Series is the handheld model of the electric-powered line, delivering cleaning capability up to 1400 PSI. The ET features a reliable direct-drive triplex pump and is ETL safety certified.



Note: Detergent injector sold separately

- 1725 RPM Motor
- Direct-drive high-pressure pump
- 25' & 50' hose
- Convenient carrying handle
- Remote switch with 10' cord (ET-201409DX2 only)
- Standard Auto Start/Stop (ET-201409DX2 only)



MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	PUMP MODEL	HOSE (FT)	DIMENSIONS (LXWXH)	SHIP WT (LBS)
ET-301109D	1.106-107.0	3.0	1000	2.0	115/1	HF2830S	50	20"x19"x17"	121
ET-201409DX2	1.107-089.0	1.8	1400	2.0	115/1	HF2030S	25	20"x19"x17"	123

OPTIONS

PART NO.	DESCRIPTION
8.920-952.0	Wall Mount Bracket
8.929-062.0	Detergent Injector (up to 3 GPM)

HOT BOX OIL-FIRED

Add hot water cleaning economically. Portable water heater add-on for existing cold water pressure washers. Quick connect to cold water washer, supply fuel and power to Hot Box for hot water cleaning applications — USE ONLY WHEN NEEDED and keep the convenience of the portable cold water washer.

- Heater add-on
- 3000 PSI
- Diesel, kerosene, #1 heating oil
- 3/8" QC inlet / outlet
- Efficient vertical combustion
- 5-gallon polyethylene fuel tank
- 36' ground fault interrupter plug
- Thermostat temperature control
- Compact size
- 10" easy-roll tubed pneumatic tires



MODEL	PART NO.	GPM	PSI	VOLT/PH	DIMENSIONS (LXWXH)
HOT BOX	1.103-910.0	Up to 5	Up to 3,000	120/1	27"x37"x39"

RC SERIES WATER RECOVERY

Stop wash water from flowing down a drain or away from your area by collecting the wastewater from pressure washing. As EPA laws become more prevalent and strive to conserve water quality, contract cleaners and construction sites will need to recover their wash water and runoff. Eliminate the problem with the RC Series that is capable of recovering and transferring up to 30 GPM of water and transferring to a holding tank. Its small footprint allows the RC Series to be mounted on a trailer. Be fully in control of water flow with the optional water dikes and drain covers to stop water from flowing down a drain or away from your site. Comes standard with a 50' vacuum hose and scupper head.

- 3 stage vacuum motor delivers 100 CFM 100" sealed lift vacuum
- Simple curbside controls for easy use
- Rated for water up to 120°F and compatible with surface cleaners and hot water machines
- Bolt-on mounting system configured on the base to mount to a trailer for portability from site to site or optional caster wheel kit
- Small footprint allows the unit to be mounted on single axle trailers
- Drain port and filter basket work together to keep sludge from clogging



MODEL	PART NO.	ELECTRICAL	AMPS	RECOVERY	TANK (GAL)	VACUUM MOTOR	DIMENSIONS (LXWXH)	SHIP WT (LBS)
RC-30E	1.103-514.0	120V	15	30 GPM	27	3 Stage 100 CFM 100" sealed lift	24"x27"x59"	127

OPTIONS (FIELD INSTALLED)

PART NO.	DESCRIPTION
8.751-299.0	Mosmatic Surface Cleaner with Vac Port
8.928-887.0	Caster Wheel Kit
8.925-858.0	Discharge Hose Kit
8.618-451.0	Vacuum Hose
8.928-850.0	Scupper Head

DRAIN COVERS & WATER DIKES

PART NO.	DESCRIPTION
8.751-135.0	Drain Cover, 36" x 36", 30oz PVC
8.751-136.0	Drain Cover, 48" x 48", 30oz PVC
8.751-137.0	Drain Cover, 48" x 48", Urethane
8.751-138.0	Water Dike, 10', 22oz PVC
8.751-139.0	Water Dike, 10', 40oz Urethane
8.751-140.0	Water Dike, 20', 22oz PVC
8.751-141.0	Water Dike, 20', 40oz Urethane