

333 MODEL

The 333 Model is a competitively priced, entry-class hot water pressure washer. Innovative upright design ensures good mobility and ergonomics, while its compact size makes it easy to transport both horizontally and vertically. Built-in 3 angle spray nozzle and low pressure chemical application. Very user-friendly with one-switch operation and areas for hose and accessory storage. Equipped with a 33' high-pressure hose and 16' power cord.




- Oil-Fired Heater
- 1.7 GMP @ 1200 PSI
- Auto Start/Stop



MODEL	PART NO.	GPM	PSI	HP	VOLT/ PH	AMPS	FUEL	BTU/HR	PUMP MODEL	PORTABILITY	DIMENSIONS (LXWXH)	SHIP WT (LBS)
333	1.064-049.0	1.7	1200	2.3	115/1	12.5	Oil	80,000	Axial	Std	28"x28"x46"	178

OPTIONS	
PART NO.	DESCRIPTION
2.642-305.0	Gutter cleaning lance (<i>image 1 below</i>)
4.760-245.0	Underbody lance (<i>image 2 below</i>)
6.390-025.0	High-pressure hose, 10m DN8, extension piece
6.401-459.0	Plug nipple
6.390-028.0	Pipe cleaning hose
4.762-010.0	Wet blasting attachment (<i>image 3 below</i>)

OPTIONS	
PART NO.	DESCRIPTION
2.638-526.0	Nozzle kit for wet blasting attachment
2.640-355.0	FR30Me surface cleaner (<i>image 4 below</i>)
2.640-482.0	Nozzle kit for surface cleaner FR
2.883-803.0	Power nozzle 25° spray angle
3.637-170.0	Detergent injector for high pressure



500 SERIES & MODEL 680SS

The 500 Series delivers rugged, yet affordable, cleaning power for a broad range of applications, from agriculture to building maintenance. The sporty 555SS, with its stainless steel coil skin, is our most popular entry level hot water model—compact, evenly balanced, easy to maneuver, and engineered with the operator in mind. As with the entire Hotsy line, all models in the 500 series are ETL safety certified to UL-1776, with Hotsy pumps backed by a 7-year limited warranty. A pressure relief valve is standard on all 500 Series models. Equipped with a 50' hose.

- Oil-Fired or LP-Fired
- 115V/1PH
- 1725 RPM Direct-Drive Pump
- Flat-Free Tires for Easy Handling



Model 555SS



Model 558-Propane (shown with optional Portagear & propane tank)



Model 560SS



Model 680SS

MODEL	PART NO.	GPM	PSI	HP	VOLT/ PH	AMPS	FUEL	BTU/HR	PUMP MODEL	PORTABILITY	DIMENSIONS (LXWXH)	SHIP WT (LBS)
555SS	1.109-033.0	2.2	1300	2	115/1	20	Oil	214,300	Duplex - HHC165L.1	Std	33"x27"x41.5"	360
558	1.109-610.0	2.2	1300	2	115/1	18	LP	214,300	Duplex - HHC165L.1	Optional	31.5"x26"x41"	350
560SS	1.109-034.0	2.1	1500	2.3	115/1	20	Oil	214,300	Triplex - HHC205L.1	Std	33"x26"x44"	395
680SS	1.109-035.0	3	1000	2	115/1	20	Oil	289,900	Triplex - HF2830S	Std	33"x27"x45.5"	405

SS=Stainless Steel

OPTIONS	
PART NO.	DESCRIPTION
8.717-728.0	8" LP Gas-Fired Draft Diverter (Model 558)
8.717-764.0	8" Oil-Fired Vent Regulator (555SS, 560SS & 680SS)
8.903-049.0	Portagear (Model 558)

OPTIONS	
PART NO.	DESCRIPTION
8.717-791.0	Propane Tank, 43 lb. (Model 558)
8.903-034.0	Float Tank, 555SS (Field Install)
8.750-486.0	360° Pivot Reel, 100' (fits all 500 Series EXCEPT 558)

700 SERIES & MODEL 895SS

DIRECT DRIVE **BELT DRIVE**

The 700 Series offers a nice balance of Hotsy ruggedness and cleaning performance, yet the affordability of an entry-level machine. In addition to the two direct-drive models, this series also offers belt-drive models that clean at 3.0 GPM and 2000 PSI. More powerful yet is the 895SS. The multiple fuel and electrical options makes the 700 series ideal for meeting the needs of commercial customers. All models are ETL safety certified and feature the Hotsy Triplex pump with a 7-year limited warranty. A pressure relief valve is standard on all 700 Series models. Equipped with a 50' hose.

- Oil-, LP-, or Natural Gas-Fired
- Direct- & Belt-Drive
- Flat-Free Tires for Easy Handling



Model 795SS



Model 895SS



Model 771-Propane (shown with optional Portagegear & Propane Tank)

MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	AMPS	FUEL	BTU/HR	PUMP MODEL	DRIVE	PORTABILITY	DIMENSIONS (LXWXH)	SHIP WT (LBS)
771	1.109-611.0	3.0	1500	3	230/1	13	LP	280,000	HHC235R.1	Direct	Optional	32"x27"x45.5"	415
772	1.109-037.0	3.0	1500	3	230/1	13	NG	338,000	HHC235R.1	Direct	N/A	32"x27"x45.5"	415
790SS	1.109-612.0	3.0	2000	4	230/1	20	Oil	289,900	HB4025R	Belt	Std	37"x28"x45.5"	450
795SS	1.109-039.0	3.5	2000	5	230/1	24	Oil	289,900	HB4025R	Belt	Std	37"x28"x45.5"	455
795SS-208	1.109-040.0	3.5	2000	5	208/1	27	Oil	289,900	HB4025R	Belt	Std	37"x28"x45.5"	500
895SS	1.109-077.0	3.5	3000	8.2	230/1	36	Oil	289,900	HHC506R.1	Belt	Std	37"x28"x45.5"	480

SS = Stainless Steel

OPTIONS	
PART NO.	DESCRIPTION
8.717-728.0	8" Natural Gas- or LP Gas-Fired Draft Diverter (771, 772)
8.717-764.0	8" Oil-Fired Vent Regulator (790SS, 795SS, 895SS)
8.903-049.0	Portagegear, Model 771

OPTIONS	
PART NO.	DESCRIPTION
8.717-791.0	Propane Tank, 43 lb.
8.750-486.0	360° Pivot Reel, 100'
8.750-483.0	360° Pivot Reel, 200' (fits all models except 771, 772)

800 SERIES

BELT DRIVE

Rugged design, easy maneuverability and massive cleaning power. Comparable to the cleaning power of Hotsy's heavy-duty stationary units, the big and beefy 800 Series is surprisingly easy to maneuver into place, allowing you to tackle the heaviest of industrial cleaning jobs. The 28" wide wheel base helps with stability, yet is narrow enough to fit easily through doorways. Components are protected by an easy-to-remove cover allowing servicing access. All 800 series hot water pressure washers are backed by a 7-year limited warranty on the Hotsy Triplex pump. A pressure relief valve, upstream detergent injector and stainless steel coil wrap are standard features on all 800 Series models, which are ETL certified. Equipped with a 50' hose.

U.S. Design Patent No. 726,382 S

- Oil-Fired
- Belt drive Hotsy pump
- Big & Beefy, Yet Easy To Maneuver
- Rugged Hotsy Pump with 7-Year Limited Warranty
- Stainless Steel Coil Skin



Shown with optional hose reel



MODEL	PART NO.	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMPS	FUEL	BTU/HR	PUMP MODEL	PORTABILITY	DIMENSIONS (LXWXH)	SHIP WT (LBS)
821	1.109-120.0	4.0	2300	6.2	3450	208/1	33	Oil	381,000	HM4045R.3	Std	51"x28"x51"	632
842	1.109-121.0	4.0	2000	5	1725	208/3	20	Oil	381,000	HM4030R.3	Std	51"x28"x51"	622
843	1.109-122.0	4.0	2000	5	1725	230/1	29	Oil	381,000	HM4030R.3	Std	51"x28"x51"	622
844	1.109-123.0	4.0	2000	5	1725	230/3	19	Oil	381,000	HM4030R.3	Std	51"x28"x51"	622
845	1.109-124.0	4.0	2000	5	1725	460/3	10	Oil	381,000	HM4030R.3	Std	51"x28"x51"	691
851	1.109-125.0	4.0	3000	8.2	3450	208/1	44	Oil	381,000	HM4045R.3	Std	51"x28"x51"	675
852	1.109-126.0	4.0	3000	7.5	1725	208/3	25	Oil	381,000	HM4030R.3	Std	51"x28"x51"	665
853	1.109-127.0	4.0	3000	7.5	1725	230/1	37	Oil	381,000	HM4030R.3	Std	51"x28"x51"	665
854	1.109-128.0	4.0	3000	7.5	1725	230/3	25	Oil	381,000	HM4030R.3	Std	51"x28"x51"	665
855	1.109-129.0	4.0	3000	7.5	1725	460/3	14	Oil	381,000	HM4030R.3	Std	51"x28"x51"	665
856	1.109-130.0	4.0	3000	8.2	3450	575/3	11	Oil	381,000	HM4045R.3	Std	51"x28"x51"	680
873	1.109-131.0	5.0	3000	10	1725	230/1	42	Oil	404,000	HM4030R.3	Std	51"x28"x51"	670
874	1.109-132.0	5.0	3000	10	1770	230/3	29	Oil	404,000	HM4030R.3	Std	51"x28"x51"	675

OPTIONS

PART NO.	DESCRIPTION
8.930-170.0	Auto Start/Stop Kit (Field Installed)*
8.930-172.0	Thermal Shutdown Kit (Field Installed)
8.930-171.0*	Time Delay Shutdown (Field Installed)*
8.717-764.0	8" Oil-Fired Vent Regulator

* Note: Time Delay Shutdown and Auto Start/Stop cannot be combined on the same machine.

OPTIONS

PART NO.	DESCRIPTION
8.750-486.0	360° Pivot Reel, 100'
8.750-483.0	360° Pivot Reel, 200'
8.711-907.0	Pneumatic Wheel - 12 1/2" (4 required)
8.923-225.0	Detergent Bucket Bracket

900/1400 SERIES

BELT DRIVE

Hotsy's 900/1400 Series of innovative stationary models are packed with standard features! The most impressive is the programmable smart control automation. Safety is key with a pressure relief valve and locking lid and side panels around the belt and pulleys to keep users safe. These electric-powered washers are available in either LP or Natural Gas fired models. New models have the same footprint as previous generations, so users can feel confident about upgrading. Panels may be easily removed for access to the machine components for servicing. All models are ETL certified to the rigid UL-1776 safety standards. Features a Hotsy highly efficient Triplex pump. Equipped with a 50' hose.

U.S. Design Patent No. 740,501 S

- LP-or Natural Gas-Fired
- Belt-Drive Hotsy Pump
- Remote-Ready
- Smart Relay Control provides control over run time, auto start/stop and shut down functionality



MODEL	PART NO.	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMPS	FUEL	BTU/HR	PUMP MODEL	DIMENSIONS (LXWXH)	SHIP WT (LBS)
921P	1.109-948.0	4.0	2300	6.2	3450	208/1	32	LP	364,835	HM4030R.3	47.5"x21"x51"	700
921N	1.109-691.0	4.0	2300	6.2	3450	208/1	32	NG	364,835	HM4030R.3	47.5"x21"x51"	700
926P	1.109-949.0	4.0	2000	5	1800	575/3	7	LP	364,835	HM4030R.3	47.5"x21"x51"	660
926N	1.109-692.0	4.0	2000	5	1800	575/3	7	NG	364,835	HM4030R.3	47.5"x21"x51"	660
942P	1.109-693.0	4.0	2000	5	1725	208/3	18	LP	360,997	HM4030R.3	47.5"x21"x51"	590
942N	1.109-694.0	4.0	2000	5	1725	208/3	18	NG	364,835	HM4030R.3	47.5"x21"x51"	655
943P	1.109-695.0	4.0	2000	5	1725	230/1	25	LP	360,997	HM4030R.3	47.5"x21"x51"	685
943N	1.109-696.0	4.0	2000	5	1725	230/1	25	NG	364,835	HM4030R.3	47.5"x21"x51"	685
944P	1.109-697.0	4.0	2000	5	1725	230/3	16	LP	360,997	HM4030R.3	47.5"x21"x51"	580
944N	1.109-698.0	4.0	2000	5	1725	230/3	16	NG	364,835	HM4030R.3	47.5"x21"x51"	680
945P	1.109-699.0	4.0	2000	5	1725	460/3	8	LP	360,997	HM4030R.3	47.5"x21"x51"	585
945N	1.109-700.0	4.0	2000	5	1725	460/3	8	NG	364,835	HM4030R.3	51"x28"x51"	670

MODEL	PART NO.	GPM	PSI	HP	MOTOR VRPM	VOLT/PH	AMPS	FUEL	BTU/HR	PUMP MODEL	DIMENSIONS (LXWXH)	SHIP WT (LBS)
1451P	1.109-950.0	3.5	3000	7.5	3450	208/1	39	LP	364,835	HM4030R.3	47.5"x21"x51"	730
1451N	1.109-701.0	3.5	3000	7.5	3450	208/1	39	NG	364,835	HM4030R.3	47.5"x21"x51"	730
1452P	1.109-702.0	3.5	3000	7.5	1725	208/3	24	LP	360,997	HM4030R.3	47.5"x21"x51"	625
1452N	1.109-703.0	3.5	3000	7.5	1725	208/3	24	NG	364,835	HM4030R.3	47.5"x21"x51"	625
1453P	1.109-704.0	3.5	3000	7.5	1725	230/1	34	LP	360,997	HM4030R.3	47.5"x21"x51"	735
1453N	1.109-705.0	3.5	3000	7.5	1725	230/1	34	NG	364,835	HM4030R.3	47.5"x21"x51"	735
1454P	1.109-706.0	3.5	3000	7.5	1725	230/3	24	LP	360,997	HM4030R.3	47.5"x21"x51"	625
1454N	1.109-707.0	3.5	3000	7.5	1725	230/3	24	NG	364,835	HM4030R.3	47.5"x21"x51"	700
1455P	1.109-708.0	3.5	3000	7.5	1725	460/3	12	LP	360,997	HM4030R.3	47.5"x21"x51"	630
1455N	1.109-709.0	3.5	3000	7.5	1725	460/3	12	NG	364,835	HM4030R.3	47.5"x21"x51"	780
1456P	1.109-951.0	3.5	3000	8.2	3450	575/3	10	LP	364,835	HM4030R.3	47.5"x21"x51"	621
1456N	1.109-710.0	3.5	3000	8.2	3450	575/3	10	NG	364,835	HM4030R.3	47.5"x21"x51"	621
1473P	1.109-711.0	5.0	3000	10	1725	230/1	42	LP	378,617	HM4035R.3	47.5"x21"x51"	735
1473N	1.109-713.0	5.0	3000	10	1725	230/1	42	NG	390,025	HM4035R.3	47.5"x21"x51"	735
1474P	1.109-712.0	5.0	3000	10	1770	230/3	29	LP	378,617	HM4035R.3	47.5"x21"x51"	740
1474N	1.109-714.0	5.0	3000	10	1770	230/3	29	NG	390,025	HM4035R.3	47.5"x21"x51"	740
1475P	1.109-952.0	5.0	3000	10	1725	208/3	34	LP	378,617	HM4030R.3	47.5"x21"x51"	740
1475N	1.109-953.0	5.0	3000	10	1725	208/3	34	NG	378,617	HM4030R.3	47.5"x21"x51"	740

* Includes connectors and flue outlet

900/1400 SERIES OPTIONS

OPTIONS

PART NO.	DESCRIPTION
8.916-989.0	Remote Station (<i>image 1 below</i>)
8.916-988.0	Soap Solenoid and Switch
8.717-728.0	8" Natural Gas- or LP Gas-Fired Draft Diverter
9.803-452.0	Water Inlet Solenoid (Field Installed)
8.755-253.0	8" Power Dampener
8.749-807.0	Power Dampener Wiring Harness

OPTIONS

PART NO.	DESCRIPTION
8.924-814.0	R-Con Wireless Remote Kit (1 remote/1 receiver) (<i>image 2 below</i>)
8.925-072.0	R-Con Wireless Remote Kit (2 remotes/1 receiver)
8.924-878.0	Wall Mount Remote Bracket for R-Con (<i>image 3 below</i>)
8.756-329.0	Replacement Remote (transmitter only)



1800 SERIES

BELT DRIVE

The 1800 Series provides stationary cleaning with hot water indoors. The 7 models are electric-powered and natural gas, oil or optional LP gas-heated. The coil skin comes standard with stainless steel. The sleek cabinet has removeable side and front panels, making it easy for routine scheduled maintenance and service. The Smart Relay allows the washer to be customized to individual needs, and is protected behind the front panel. All models are certified to the rigid UL-1776 safety standards and feature the highly efficient Hotsy Triplex pump. A pressure switch is a standard feature on all 1800 Series models. Equipped with a 50' hose.

- Natural Gas, Oil or optional LP-Fired
- Belt Drive Pump
- Smart Relay Control provides control over run time, auto start/stop and shut down functionality



MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	AMPS	FUEL	BTU/HR	PUMP MODEL	DIMENSIONS (LXWXH)	SHIP WT (LBS)
1812SS	1.109-660.0	6.0	2500	10	230/1	42	NG	558,050	HX9536L.2	51"x31"x53.25"	1,020
1830SS	1.109-665.0	6.0	3000	15	230/3	40	Oil*	579,776	HX9536L.2	51"x31"x53.25"	1,020
1832SS	1.109-662.0	6.0	3000	15	230/3	38	NG	558,050	HX9536L.2	51"x31"x53.25"	1,020
1832SS-208	1.109-661.0	6.0	3000	15	208/3	41	NG	558,050	HX9536L.2	51"x31"x53.25"	1,020
1833SS	1.109-666.0	6.0	3000	15	460/3	21	Oil*	579,776	HX9536L.2	51"x31"x53.25"	1,020
1835SS	1.109-663.0	6.0	3000	15	460/3	19	NG	558,050	HX9536L.2	51"x31"x53.25"	1,020
1836SS	1.109-664.0	6.0	3000	15	575/3	16	NG	558,050	HX9536L.2	51"x31"x53.25"	1,020

SS = Stainless Steel
 *Oil-fired models are not supplied with a fuel tank

OPTIONS	
PART NO.	DESCRIPTION
8.916-989.0	Remote Station (<i>image 1 below</i>)
8.916-988.0	Soap Solenoid and Switch
8.749-806.0	10" Power Dampener
8.749-807.0	Power Dampener Wiring Harness
8.903-074.0	LP Conversion Kit (Factory Installed)
9.801-040.0	10" Natural Gas- or LP Gas-Fired Draft Diverter

OPTIONS	
PART NO.	DESCRIPTION
9.803-452.0	Water Inlet Solenoid (Field Installed)
8.924-814.0	R-Con Wireless Remote Kit (1 remote /1 receiver) (<i>image 2 below</i>)
8.925-072.0	R-Con Wireless Remote Kit (2 remotes/1 receiver)
8.924-878.0	Wall Mount Remote Bracket for R-Con (<i>image 3 below</i>)
8.756-329.0	Replacement Remote (transmitter only)



5700/5800 SERIES

BELT DRIVE

The 5700 and 5800 Series produces a powerful punch and is ideal for wash bay installations. With its 20 HP motor driving the incomparable Hotsy Triplex Pump and a vertical banded belt, the 5700 and 5800 Series delivers cleaning power up to 9.5 GPM and 3000 PSI. Has a sleek cabinet with removeable panels for easy access for maintenance. A removeable control panel provides access to the adjustable temperature control and the Smart Relay for secured control of operating positions. Remote ready for wash bay installations. All models are stationary and certified to the rigid UL-1776 safety standards. Equipped with a 50' hose.

- Oil, Natural Gas or optional LP-Fired
- Belt Drive Pump
- Smart Relay Control provides control over run time, auto start/stop and shut down functionality



MODEL	PART NO.	GPM	PSI	HP	VOLT/ PH	AMPS	FUEL	BTU/HR	PUMP MODEL	HOSE (FT)	DIMENSIONS (LXWXH)	SHIP WT (LBS)
5730SS	1.109-658.0	8.0	3000	20	230/3	44	Oil*	768,000	HX9536L.2	50	51"x31"x63.4"	1,471
5732SS-208	1.109-654.0	8.0	3000	20	208/3	55	NG	720,450	HX9536L.2	50	51"x31"x63.4"	1,471
5732SS	1.109-655.0	8.0	3000	20	230/3	42	NG	720,450	HX9536L.2	50	51"x31"x63.4"	1,471
5733SS	1.109-659.0	8.0	3000	20	460/3	23	Oil*	768,000	HX9536L.2	50	51"x31"x63.4"	1,471
5735SS	1.109-656.0	8.0	3000	20	460/3	21	NG	720,450	HX9536L.2	50	51"x31"x63.4"	1,471
5736SS	1.109-657.0	8.0	3000	20	575/3	16	NG	720,450	HX9536L.2	50	51"x31"x63.4"	1,471
5832SS	1.109-651.0	9.5	2500	20	230/3	42	NG	939,890	HX1036L.2	50	51"x31"x63.4"	1,471
5832SS-208	1.109-650.0	9.5	2500	20	208/3	48	NG	939,890	HX1036L.2	50	51"x31"x63.4"	1,471
5835SS	1.109-652.0	9.5	2500	20	460/3	21	NG	939,890	HX1036L.2	50	51"x31"x63.4"	1,461
5836SS	1.109-653.0	9.5	2500	20	575/3	16	NG	939,890	HX1036L.2	50	51"x31"x63.4"	1,471

SS = Stainless Steel

*Oil-fired models are not supplied with a fuel tank

OPTIONS

PART NO.	DESCRIPTION
8.916-916.0	LP Conversion Kit, 5700 (Factory Installed)
8.916-915.0	LP Conversion Kit, 5800 (Factory Installed)
8.753-171.0	12" Power Dampener
8.749-807.0	Power Dampener Wiring Harness
9.803-452.0	Water Inlet Solenoid (Field Installed)
8.916-989.0	Remote Station (<i>image 1 below</i>)

OPTIONS

PART NO.	DESCRIPTION
8.916-988.0	Soap Solenoid and Switch
8.717-730.0	12" Natural Gas- or LP Gas-Fired Draft Diverter
8.924-814.0	R-Con Wireless Remote Kit (1 remote/1 receiver) (<i>image 2 below</i>)
8.925-072.0	R-Con Wireless Remote Kit (2 remotes/1 receiver)
8.924-878.0	Wall Mount Remote Bracket for R-Con (<i>image 3 below</i>)
8.756-329.0	Replacement Remote (transmitter only)



GAS ENGINE SERIES

DIRECT DRIVE

The Gas Engine Series consists of the most compact and portable hot water pressure washers on the market. Powered by reliable gasoline engines, all you need is water and you can clean anywhere anytime. The five models offer a broad range of cleaning power, from 2.7 to 4.0 GPM and from 2400 to 3500 PSI. All models feature Hotsy's highly efficient Triplex pump backed by Hotsy's 7-year pump limited warranty and all are ETL safety certified. All models are equipped with a standard pressure switch and 50' hose.

- Oil-Fired
- 12 Volt DC
- Direct Drive
- 3 Battery-less Models
- 2 Electric-Start Models
- Flat-Free Tires for Easy Handling



965SS



1075SSE

MODEL	PART NO.	GPM	PSI	ENGINE/MODEL	CCs	BURNER	BTU/HR	PUMP MODEL	PORTABILITY	DIMENSIONS (LXWXH)	SHIP WT (LBS)
871SS*	1.110-014.0	2.7	2400	Kohler CH270	208	12V DC	248,500	HP3035G	Std	43"x27"x39"	410
965SS*	1.110-015.0	3.0	3000	Honda GX270	270	12V DC	248,500	HP3035G	Std	47"x31"x41"	445
1065SS*	1.110-010.0	3.5	3000	Honda GX340	337	12V DC	309,900	HS3540G.3	Std	47"x31"x45"	495
1065SSE†	1.110-011.0	3.5	3000	Honda GX340	337	12V DC	309,900	HS3540G.3	Std	47"x31"x45"	510
1075SSE†	1.110-012.0	4.0	3500	Honda GX390	389	12V DC	309,900	HS4040G.3	Std	47"x31"x45"	520

*Battery not required
 † 12V battery required, but not supplied
 E = Electric-start engine

GAS ENGINE SERIES

BELT DRIVE

The belt drive versions of the Gas Engine Series provide versatility with the roll cage design. Designed to fit the needs of the end-user, this versatile hot water washer converts easily to a skid unit, portable with wheels or a wheel/caster kit, or can be mounted on a trailer. Powered by reliable gasoline engines, the three models offer a broad range of cleaning power, from 3.0 to 4.6 GPM and from 3000 to 3500 PSI. All models feature the Hotsy Triplex pump backed by Hotsy's 7-year pump limited warranty and all are ETL safety certified. All models are equipped with a standard pressure switch and 50' hose.

- Oil-Fired
- 12 Volt DC
- Belt Drive
- 2 Electric-Start Models



1075BE
(shown with optional
caster wheel kit)



965B (shown with optional
pneumatic tires)



1080BE (shown with optional stainless
steel coil wrap and skid rails)

MODEL	PART NO.	GPM	PSI	ENGINE MODEL	CCs	BURNER	BTU/HR	PUMP MODEL	PORTABILITY	DIMENSIONS (LXWXH)	SHIP WT (LBS)
965B*	1.110-565.0	3.0	3000	Honda GX270	270	12V DC	248,500	HD3030L.1	Optional	42"x27.5"x39"	590
1075BE†	1.110-566.0	4.0	3500	Honda GX390	389	12V DC	385,800	HM4035L.3	Optional	42"x27.5"x39"	625
1080BE†	1.110-567.0	4.6	3500	Briggs VAN 18	570	12V DC	385,800	HM4035L.3	Optional	42"x27.5"x39"	665

* Battery not required
 † 12V battery required, but not supplied
 E= Electric-start engine
 B= Belt Drive

OPTIONS

PART NO.	DESCRIPTION
8.916-172.0	Float Tank Kit (includes high pressure detergent kit), 1075BE & 1080BE models
8.916-173.0	Float Tank Kit (includes high pressure detergent kit) 965B model
8.931-259.0	Skid Rail Kit (Field Installed)- adds 3.875" to height
8.931-260.0	Caster Kit - 2 casters / 2 wheels (Field Installed) - adds 7.5" to height
8.931-261.0	Pneumatic Tire Kit with Handle Bar (Field Installed) - adds 10" to width, 6" to height
8.916-175.0	High Pressure Detergent Kit, 1075BE & 1080BE models (to be used with a remote water tank)
8.916-174.0	High Pressure Detergent Kit, 965B models (to be used with a remote water tank)
8.915-274.0	Stainless Steel Coil Wrap (Field Installed)

1200 SERIES

BELT DRIVE

The 1200 Series delivers some serious on-site, hot water cleaning capability of up to 6 GPM and 4000 PSI. Rugged gasoline engines all have electric start. Five models come with a 2000W generator. The self-contained cleaning units are built to hold up under the toughest of conditions. All feature the Hotsy Triplex pump, with its 7-year limited warranty and ETL safety certification (CSA-Certified for non-generator models). All 1200 Series models are equipped with a standard flow switch and 50' hose.

- Gas/Diesel-Powered
- Oil-Fired
- Belt Drive
- Electric Start



1260SS



1270SS (shown with optional Portage Kit)

MODEL	PART NO.	GPM	PSI	ENGINE MODEL	FUEL	CCs	BURNER	BTU/HR	PUMP MODEL	DIMENSIONS (LXWXH)	SHIP WT (LBS)
1260SS	1.110-533.0	4.5	3000	Briggs VAN 18	Gas	570	12V DC	414,318	HM4035R.2	45"x33"x52"	745
1260SSG*	1.110-535.0	4.5	3000	Briggs VAN 18	Gas	570	120V AC	414,318	HM4035R.2	45"x33"x52"	830
1270SS	1.110-557.0	4.5	4000	Honda GX630	Gas	688	12V DC	414,318	HX5843R.2	45"x33"x52"	855
1270SSG*	1.110-536.0	4.5	4000	Honda GX630	Gas	688	120V AC	414,318	HX5843R.2	45"x33"x52"	870
1280SS	1.110-558.0	5.1	3500	Honda GX630	Gas	688	12V DC	414,318	HX8043R.2	45"x33"x52"	760
1280SSG*	1.110-537.0	5.1	3500	Honda GX630	Gas	688	120V AC	414,318	HX8043R.2	45"x33"x52"	750
1290SS	1.110-538.0	5.6	3000	Honda GX630	Gas	688	12V DC	456,344	HX8043R.2	45"x33"x52"	744
1290SSG*	1.110-539.0	5.6	3000	Honda GX630	Gas	688	120V AC	456,344	HX8043R.2	45"x33"x52"	905
1291SS	1.110-075.0	8.0	3000	Honda GX660	Gas	688	12V DC	407,826	HX9536R	45"x33"x52"	760
1291SSG*	1.110-076.0	8.0	3000	Honda GX660	Gas	688	120V AC	407,826	HX9536R	45"x33"x52"	920
1265SSD	1.110-073.0	4.5	3000	Kubota Z602-E4B	Diesel	599	12V DC	414,318	HM4035	45"x33"x52"	795
1265SSDS**	1.110-074.0	4.5	3000	Kubota Z602-E4B	Diesel	599	12V DC	414,318	HM4035	45"x33"x52"	795

* Models include a 2000W generator

** Models include stainless frame

12V battery is required for all models, but is not supplied

OPTIONS

PART NO.	DESCRIPTION
8.903-025.0	Portage Kit (all models)

HSS & HSDS SERIES SUPERSKID

BELT DRIVE

The Super Skid HSS Series is by far, the largest and most powerful of Hotsy's hot water pressure washers. The Super Duty HSDS models feature a Hawk pump with lower RPM for long lasting durability; there's literally nothing else on the market as robust, big & powerful. HSS models come standard with the reliable Hotsy triplex belt-driven high-pressure pump. Triple banded belt for more efficient power transmission. Models are powered by a 16 & 24 HP Kubota engines with electric start and all feature a 3/4-inch foil-backed insulated Schedule 80 heating coil with stainless steel skin and 5-year warranty. Two fuel tanks for longer operation, a high-efficiency Wayne burner and optional dual gun kit allows two users at one time.



- Diesel-Powered
- Diesel-Fired
- Belt Drive
- Electric Start



MODEL	PART NO.	GPM	PSI	ENGINE MODEL	CCs	BURNER	BTU/HR	PUMP MODEL	HOSE	DIMENSIONS (LXWXH)	SHIP WT (LBS)
HSS-503069E	1.110-604.0	5.0	3000	Kubota Z602-E4B	599	12V DC	465,000	HX5843R.2	50'-3/8"	73"x37"x64"	1305
HSS-653569E	1.110-605.0	6.5	3500	Kubota D1105-E4B	1123	12V DC	565,000	HX8043R.2	50'-3/8"	73"x37"x64"	1710
HSS-803069E	1.110-606.0	8.0	3000	Kubota D1105-E4B	1123	12V DC	635,000	HX9536.2	50'-1/2"	73"x37"x64"	1715
HSS-952569E	1.110-607.0	9.5	2500	Kubota D1105-E4B	1123	12V DC	780,000	HX1036R.2	50'-1/2"	73"x37"x64"	1715

SUPER DUTY MODELS:

MODEL	PART NO.	GPM	PSI	ENGINE MODEL	CCs	BURNER	BTU/HR	PUMP MODEL	HOSE	DIMENSIONS (LXWXH)	SHIP WT (LBS)
HSDS-503069E	1.110-616.0	5.0	3000	Kubota Z602-E4B	599	12V DC	465,000	HHP2750R	50'-3/8"	73"x37"x64"	1610
HSDS-653569E	1.110-617.0	6.5	3500	Kubota D1105-E4B	1123	12V DC	565,000	HHP3650R	50'-3/8"	73"x37"x64"	2005
HSDS-803069E	1.110-618.0	8.0	3000	Kubota D1105-E4B	1123	12V DC	635,000	HFR40FR	50'-1/2"	73"x37"x64"	2015
HSDS-952569E	1.110-619.0	9.5	2500	Kubota D1105-E4B	1123	12V DC	780,000	HFR60FR	50'-1/2"	73"x37"x64"	2020

All models are Electric Start. 12V battery is required for all models, but is not supplied.

OPTIONS

PART NO.	DESCRIPTION
8.923-164.0	Dual Gun Kit - includes necessary fittings, extra hose gun and wand (Field installed)
8.923-125.0	Steam Kit - includes necessary fittings and panel mount control valve (Field installed)
8.923-124.0	Float Tank Kit - includes float tank, necessary fittings and panel mount detergent metering valve (Field installed)



Pump size comparison:
The HFR and HHP pumps from Leuco used in the Super Duty models dwarf the standard HX.

HWE SERIES ALL-ELECTRIC

BELT DRIVE

The HWE Series is powered and heated by electricity, making it ideal for indoor use. It's a quiet machine with no fumes, making it ideal for food service and in-plant cleaning. Water is heated in a stainless steel heating coil, immersed in a tank of water solution, allowing for instant hot water once you pull the trigger. The heating elements do not come in contact with the pressurized water, which results in less maintenance and minimizes scale build up. The HWE features a Baldor motor, which drives a belt-drive Hotsy Triplex pump, with 7-year limited warranty, and an insulated variable pressure wand. ETL certified. Float switch is standard on the HWE Series. All models equipped with a 50' hose.



- All-Electric
- Belt Drive
- Auto Start/Stop
- Stainless Steel Coil



MODEL	PART NO.	GPM	PSI	HP	MOTOR	AMPS	VOLT/PH	KvA HOUR	BTU/HR	PUMP MODEL	DIMENSIONS (LXWXH)	SHIP WT (LBS)
HWE-402009C	1.109-646.0	4.0	2000	6.2	Baldor	55	460/3	40.5	138,308	HM4030R.3	34"x25"x52"	620
HWE-403009C	1.109-647.0	3.5	3000	7.5	Baldor	59	460/3	40.5	138,308	HM4030R.3	34"x25"x52"	640
HWE-402009F	1.109-958.0	3.5	2000	5	Baldor	46	575/3	40.5	138,308	HM4030R.3	34"x25"x52"	620
HWE-403009F	1.109-959.0	3.5	3000	7.5	Baldor	49	575/3	40.5	138,308	HM4030R.3	34"x25"x52"	640

OPTIONS

PART NO.	DESCRIPTION
8.903-042.0	Stainless Steel Washer Wrap 1700 Series (Factory installed)*
8.725-157.0	Option, Time Delay Shutdown HWE-402009C (Factory installed)**
8.725-158.0	Option, Time Delay Shutdown HWE-403009C (Factory installed)**
8.925-520.0	Option, Time Delay Shutdown HWE-403009F (Factory installed)**

*See page 33 for stainless steel and other configured options thru the Specials Dept. 575V/3Ph models only available as base unit through standard production. If adding options, go through Specials.

**Time Delay Shutdown and Auto Start/Stop cannot be combined on the same machine.